



200 Tillessen Blvd, Ridgeway, SC USA 29130

Style 1597

Generic Description: 38.30 oz. per square yard (1,299 g/m²) fancy triple weave fiberglass fabric.

Product Description: CTF Style 1597

Property	Description	Value and Tolerance		Test Method
		English	Metric	
Weave Type	Fancy Triple			ASTM D 579
Finish	Greige			
Warp count		30 +/- 2 epi	11.8 +/- 0.8 epc	ASTM D 3775
Fill count		30 +/- 2 ppi	11.8 +/- 0.8 ppc	ASTM D 3775
Warp Yarn Type		ECG 37 2/2	EC 9 134 2x2	ASTM D 4029
Fill Yarn Type		ECG 37 2/2	EC 9 134 2x2	ASTM D 4029
Selvage	Feathered	0.375 +/- 0.250 in.	9.53 +/- 6.35 mm	Visual
Roll Splice	Lapped splice	Max – 2 splices / roll Minimum 50 LY between splices	Max - 2 splices / roll Minimum 45.7 LM between splices	Roll Splice
Color	White			Visual

Physical Properties:

Property	Description	Value and Tolerance		Test Method
		English	Metric	
LOI		< 4 %	< 4 %	ASTM D 4963
Finished Weight		38.30 OSY +/- 6%	1,299 g/m ² +/- 6%	ASTM D 3776
Thickness		0.0500 +/- 0.0030 in	1.270 +/- 0.075 mm	ASTM D 1777

Packaging and Labeling

Core ID and thickness	Cardboard, 3" ID, 4" OD, 0.5" wall, 40" length
Shipping Requirements	Best Way