



200 Tillessen Blvd, Ridgeway, SC USA 29130

### Style 198

**Generic Description:** 18 oz. per square yard (610 g/m<sup>2</sup>) 2 Basket fiberglass fabric

**Product Description:** CTF Style Modified 7544

Property	Description	Value and Tolerance		Test Method
		English	Metric	
Weave Type	Basket			ASTM D 579
Finish	Greige			
Warp count		28 +/- 2 epi	11.0 +/- 0.8 epc	ASTM D 3775
Fill count		14 +/- 2 ppi	5.5 +/- 0.8 ppc	ASTM D 3775
Warp Yarn Type		ECG 37 1/2	EC9 134 1x2	ASTM D 579
Fill Yarn Type		ECG 37 2/2	EC9 134 2x2	ASTM D 579
Selvedge	Feathered	0.375 +/- 0.250	9.53 +/- 6.35	Visual
Roll Splice	Lapped splice	Max - 2 splices / roll Minimum 50 LY between splices	Max - 2 splices / roll Minimum 45.7 LM between splices	Roll Splice
Color	White			Visual

**Physical Properties:**

Property	Description	Value and Tolerance		Test Method
		English	Metric	
LOI		< 4%	< 4%	ASTM D 4963
Greige Weight		18.00 OSY +/- 6%	610 g/m <sup>2</sup> +/- 6%	ASTM D 3776
Thickness		0.024 +/- 0.003 in	0.6096 +/- 0.075 mm	ASTM D 1777

**Packaging and Labeling**

Core ID and thickness	3 in. ID, 4 in. OD. standard core
Shipping Requirements	Best way