



200 Tillessen Blvd, Ridgeway, SC USA 29130

Style 2523M

Generic Description: 11.5 oz. (390 gsm) plain weave greige fiberglass fabric

Product Description: Style 2523 Modified Yarn Input and Count

Property	Description	Value and Tolerance		Test Method
		English	Metric	
Weave Type	Plain			ASTM-D579
Finish	Greige			
Warp count		48 epi +/- 2	18.9 +/- 0.8 epc	ASTM D 3775
Fill count		20 ppi +/- 2	7.9 +/- 0.8 ppc	ASTM D 3775
Warp Yarn Type		ECG 37 1/0	EC 9 134 1x0	ASTM D 579
Fill Yarn Type		ECG 37 1/0	EC 9 134 1x0	ASTM D 579
Selvedge	Feathered	0.375 +/- 0.250	9.53 +/- 6.35	Visual
Roll Splice	Lapped	Max - 2 splices / roll Minimum 50 LY splice length	Max - 2 splices / roll Minimum 45.7 LM splice length	Roll Splice
Color	White			Visual

Physical Properties:

Property	Description	Value and Tolerance		Test Method
		English	Metric	
LOI		< 4%	< 4%	ASTM D 4963
Greige Weight		11.5 OSY +/- 6%	390 g/m ² +/- 6%	ASTM D 3776

Packaging and Labeling

Core ID and thickness	3" ID, 4" OD, 0.5" wall
Shipping Requirements	Best Way